

## SPECIFICATIONS

# NOVION UNIVERSAL CONCRETE CLEANER

### 1. PRODUCT:

NOVION UNIVERSAL CONCRETE CLEANER

### 2. DISTRIBUTOR:

NOVION, Inc.  
18 L'Hermitage Drive  
Shelton, CT 06484  
Phone: 1-800-472-0603 or 203 225-0365

Web: [www.radonseal.com](http://www.radonseal.com)  
E-mail: [novion@radonseal.com](mailto:novion@radonseal.com)

### 3. PRODUCT DESCRIPTION:

UNIVERSAL CONCRETE CLEANER is a unique formulation that removes dirt, stains, oil, adhesives, some resins and paints from concrete and masonry surfaces.

### 4. PRODUCT USES:

For industrial, commercial and residential use on sidewalks, driveways, buildings, patios, floors and walls.

### 5. JOB LIMITATIONS:

Apply in good weather on dry surface when air and surface temperatures are above 35 degrees F. Optimum temperatures are between 70-100 degrees F. Maintain unused material in closed containers in protected storage at 40-100 degrees F. Wear gloves and goggles for personal protection.

**DO NOT STORE IN STRONG SUNLIGHT OR BELOW FREEZING TEMPERATURES.**

### 6. SURFACE PREPARATION AND APPLICATION INSTRUCTIONS:

**NOTE: USE GLOVES AND GOGGLES - KEEP FROM GETTING INTO EYES.**

#### To Remove Carpet or Vinyl Flooring Adhesives

1. Scrape all loose and excessive glue. Sweep up.
2. Spread **UNIVERSAL CONCRETE CLEANER** by one of the following methods
  - a) Pour out and spread with a broom or a roller
  - b) Spray on with a compression sprayer
3. Allow to lay on surface for at least 1 1/2 – 2 hours or cover with polyethylene sheet and allow to sit overnight (the easiest). If it is hot or breezy you may need to mist the surface to keep it moist. If floor has a slope to it, the cleaner will have to be re-distributed from the low areas to the higher areas to re-moisten the high areas. Any vinyl floor backing that may have been left after the removal of old flooring will need to be scraped with a razor scraper after it has softened with the cleaner.
4. After the **UNIVERSAL CONCRETE CLEANER** has been allowed to soften and penetrate the old adhesive, start to wire brush the softened glue. (This puts cuts and scratches in the softened adhesive and allows the Cleaner to penetrate deeper)
5. When the **UNIVERSAL CONCRETE CLEANER** has sufficiently softened the adhesive, you may either hose off with strong stream or pressure wash off (the easiest and fastest)
6. Additional treatments may be required on old dried spots or extra thick deposits.

### 7. TECHNICAL DATA:

BOILING POINT:	212 Degrees F.	% VOLATILE BY VOL:	N/A
SPECIFIC GRAVITY:	.98 WT. +/- .04	pH:	10.0
SOLUBILITY IN WATER:	Excellent	VAPOR PRESSURE:	N/A
EVAPORATION RATE:	Slower than water	VAPOR DENSITY:	N/A

### 8. MSDS SHEETS:

AVAILABLE UPON REQUEST