

LastiSeal

Concrete Stain & Sealer

LastiSeal Concrete Stain & Sealer waterproofs and stains masonry in one step. Use on indoor or outdoor concrete, brick, mortar, stucco, pavers, and porous stone. LastiSeal penetrates deep into concrete (2 to 4") and hardens, which internally waterproofs and preserves masonry. The semi-translucent stain provides an attractive mottled look.

Safe and Easy to Apply

Water-based, non-toxic, nonflammable, VOC-compliant.

COVERAGE

Actual coverage depends on the substrate and porosity.

Approximate Coverage (1 application):

200–225 sq. ft./gallon on **indoor concrete**

150–200 sq. ft./gallon on **outdoor concrete and porous masonry**

If needed, approximate coverage for a second application:

250–350 sq. ft./gallon

CONDITIONS

Air and surface temperatures above 60 °F (*min.* 50 °F) but below 100 °F during and for 24 hours after application. Do not apply to hot surfaces in direct sunlight, or in strong wind. Avoid rain 24 hours before and after application. After pressure washing, let concrete dry for 72 hours.

SURFACE PREPARATION

Surface must be dry, clean, and porous! Remove paints, adhesives, efflorescence, dirt, oil, etc. Vacuum excessive dust. Concrete must be well-cured and its pH level below 9. Grinding or acid-etching will ensure surface porosity. Mask glass, metals, tiles, and plants. **Tip: Seal a small area first to confirm that the stain, when cured, does not wash off.**

APPLICATION – Stir well before and during use!

Apply LastiSeal using a low-pressure sprayer (below 30 psi) with a fan-pattern nozzle. **DO NOT OVER-APPLY!** Spray on a continuous, thick glistening film on the verge of puddling. Back-roll puddles or run-downs. If applying with a roller, maintain a wet edge.

For a more intense color, apply a light second application about half an hour later, provided the first application has readily absorbed. **Tip: If uncertain about sufficient absorption, use only one application.** Ready for foot traffic in several hours and for vehicles in 3-5 days.

CLEAN UP AND STORAGE

Clean Up: Rinse sprayer with water. **Storage:** Keep out of direct sunlight at 40-90 °F. If frozen, thaw and stir vigorously. **Shelf Life:** 1 year.

USE ONLY AS DIRECTED

CAUTION: May irritate eyes and skin. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN

FIRST AID MEASURES:

Ingestion: Drink several glasses of water. Seek medical attention if necessary.

Eye Contact: Flush eyes with water for 15 minutes.

Skin Contact: Flush with water. Remove contaminated clothing.

DISCLAIMER: We shall not be liable for any injury, loss, direct, indirect, or consequential damages arising out of the use of this product. The buyer shall determine the suitability of the product for the intended use and assumes all risk and liability whatsoever in connection with the use of this product.

For detailed application instructions or advice, consult our website or phone us.

RadonSeal

admin@radonseal.com • 1-800-472-0603 or 203-225-0367
Novion, Inc. • 18 L'Hermitage Drive • Shelton, CT 06484 • www.radonseal.com