

DryWay

Outdoor Concrete Water Repellent

Protect your driveway and outdoor concrete against water and contaminants!

DryWay Water Repellent will bead or shed water for years to come. It protects against surface water, oil spills, chloride ions, road salts, freeze-thaw damage, and airborne contaminants. It controls water-related staining and deterioration like pitting, spalling, efflorescence, rebar corrosion, cracking, molds, and algae.

This sealer does not leave a film that could peel or wear off but forms a long-lasting water-repellent barrier inside the concrete. It does not alter its appearance or texture.

DryWay is user-friendly and environmentally safe: water based, low odor, non-toxic, nonflammable, and low VOC.

COVERAGE

Rate per application:	sq. ft./gal.
Poured Concrete	150 – 200
Concrete block	80 – 120
Brick or pavers	120 – 150

Actual coverage depends on substrate porosity.

APPLICATION CONDITIONS

The substrate must be to sound, clean, and dry. After a rain, let dry for at least 24 hours. Do not apply when rain is expected within 12 hours. Air and surface temperatures should be between 45 and 90°F. Do not apply to hot surfaces in direct sunlight, or in a strong wind.

Let new concrete cure for at least 28 days. If needed, caulk, patch or repair the area prior to application.

APPLICATION PROCEDURE

Use a low-pressure sprayer (*hand-pump garden sprayer or airless*) or a paint roller.

1. Remove all paints, sealers, or adhesives. Clean off oil, grease, dirt, wax, curing compounds, efflorescence, and other contaminants that might interfere with sealer penetration.
2. **Thoroughly shake** the pail prior to opening and the sealer before use.
3. Protect glass, plants, asphalt, and other surfaces during application.
4. Apply DryWay in a **saturation film** (*on the verge of puddling*). For vertical surfaces, apply from the bottom up allowing 4–6” controlled run-down.
5. More porous surfaces may need two or more applications. Spray on additional applications “wet on wet” 5 to 10 minutes apart.
6. **Do not over-apply.** Spread out any puddles with a roller or push broom until the sealer penetrates into the substrate.

CLEAN UP

Using detergent and water, wipe off drips and overspray residue while still wet. Removing dried material may require mechanical abrasion. Clean application equipment immediately after use.

STORAGE

Store in a dry location out of direct sunlight at temperatures below 90 °F.

PROTECT FROM FREEZING.

SHELF LIFE: 1 year from shipment.

USE ONLY AS DIRECTED!

CAUTION: Causes eye irritation. May irritate skin and respiratory tract.

Avoid contact with skin eyes and clothing.

Avoid breathing mist. Use with adequate ventilation.

Wash hands thoroughly after using.

First Aid Measures

EYE: Immediately flush eyes with running water for at least 15 minutes. If adverse symptoms develop, seek medical attention.

SKIN: Wash skin with soap and water. If irritation or adverse symptoms persist, seek medical attention.

INHALATION: Remove to fresh air.

INGESTION: Drink large quantities of milk or water. Do not induce vomiting. Seek medical attention.

The supplier shall not be liable for any injury, loss, and direct or consequential damages arising out of the use of this product. The purchaser shall determine the suitability of the product for the intended use. The product is applied by the purchaser and the supplier does not provide any warranties, except as specifically stated in writing. The purchaser assumes all risks and liabilities whatsoever arising in connection with the use of this product.

RadonSeal™

Contact Us: (email) admin@radonseal.com

(toll free) 1-800-472-0603

1-203-225-0367

www.radonseal.com

Novion, Inc. • 18 L'Hermitage Drive • Shelton, CT 06484

Content: 5 U.S. gal. (18.9 L) • Made in USA