

Why RadonSeal?

waterproofs
penetrates
seals
remediates
preserves
protects
purges
extends
strengthens
reduces
usability
densifies



RadonSeal Plus Deep Penetrating Concrete Sealer

For indoor and outdoor walls, floors, and walls made of concrete or cementitious materials. Seals, stains, waterproofs, penetrates, strengthens, and restores. RadonSeal Plus penetrates, seals, and restores.

• Seals against water seepage, water vapor, and radon gas.

• Seals and strengthens concrete.

• Resists efflorescence and scaling.

• Resists water penetration.

Use RadonSeal Plus on poured concrete in good condition. Use RadonSeal Plus on masonry masonry for concrete blocks and masonry in older masonry surfaces over 20 years old.

Use 2 to 3 applications on poured concrete and 3 to 4 applications on masonry masonry.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

Apply RadonSeal Plus in a thin, uniform layer.

APPLICATION

Apply RadonSeal Plus using a low-pressure sprayer or a pump sprayer.

1. Remove any paint, wax, or oil.

2. Clean the surface with water using the sprayer or pump sprayer.

3. Thoroughly shake the seal prior to spraying.

4. Spray RadonSeal Plus on the surface in a continuous, overlapping film.

5. Do not over-apply.

6. Wipe off unabsorbed sealant with a wet rag.

7. Seal a surface in 2 days.

8. To fill more after application, hose off the surface with water and sand with a brush.

9. Reapply the sealant to the concrete floor and other floors in 2 to 3 years.

CLEAN UP

Flush the sprayer and tools with water.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

Store RadonSeal Plus in a cool, dry place.

RadonSeal Deep Penetrating Concrete Sealer is a user and environment friendly, waterborne, silicate based sealer which penetrates deep into concrete (up to 4 inches), chemically reacts, and **permanently seals concrete against water seepage, water vapor, and even minute atoms of radon gas.**

Solves Common Basement Problems!

RadonSeal Solves Common Problems Caused By Concrete's Porosity



Also protects against concrete dusting, wear, corrosion, pitting, crumbling and freeze-thaw, road salts, deicers, chemicals

Use It Around Your Home or Business! Unlike other concrete sealers, **RadonSeal delivers permanent results! No re-application is ever needed.** It does not leave a surface film therefore it **can not wear away or peel off.** RadonSeal will not change the appearance or profile of the concrete leaving the surface suitable for paints, adhesives, resurfacing, etc. Use **RadonSeal** on new or old concrete, indoor and outdoor, and concrete blocks.



- Basement Floors, Walls, or Slabs
- Driveways, Walkways, Stairs, Roofs
- Parking Garages, Water Cisterns,
- Garage Floors, Patios, Pool Decks
- Stucco, Shotcrete, Limestone, Mortar
- Retaining Walls, Ponds

Easy & Safe Application!

RadonSeal is non-toxic, nonflammable, and emits NO VOC's. Simply apply RadonSeal to bare, dry, and porous concrete using a hand-pump "garden" sprayer.

1. Dampen the concrete surface with water using your hand-pump sprayer.
2. Spray **RadonSeal** onto the damp surface in a continuous glistening film.
3. Spray on a 2nd application of **RadonSeal** 30 minutes after your 1st application (3-4 applications are required for more porous concrete).
4. In 2-3 hours after application, clean the surface with water and use of a push broom.



RadonSeal Standard or RadonSeal Plus? Use **RadonSeal Standard** for indoor and outdoor poured concrete (less than 20 years indoors or 1 year outdoors).

Use **RadonSeal Plus**, with higher mineral content, on more porous materials like concrete blocks or older poured concrete (more than 20 years indoors or 1 year outdoors).

COVERAGE (per 5-gallon pail)	CONDITIONS	CLEAN-UP & SHELF LIFE
POURED CONCRETE: 1,000 sq. ft. (in 2 applications)	<ul style="list-style-type: none"> • Air and surface temperatures must be above freezing • After a rain, let concrete dry for 2-3 days. • Do not apply to hot surfaces in direct sunlight 	<ul style="list-style-type: none"> • Clean sprayer and tools with water. • Shelf Life: 1 year from purchase
CONCRETE BLOCKS: 500 sq. ft. (in 3 applications)		
CINDER BLOCKS: 400 sq. ft. (in 4 applications)		

Protect Your Investment and Health!

Moisture problems are the most common complaint of homeowners and your basement is by far the largest source of moisture in your home. Covered floors and walls in a finished basement trap moisture and eventually cause; mold and mildew, musty odors, and dampness. Make sure to protect your investment and your health by sealing the concrete with RadonSeal.

