

# LastiSeal™

## Brick & Masonry Sealer

**LastiSeal™ Concrete & Brick Sealer is a unique, state-of-the-art waterproofing sealer.** Use on indoor or outdoor brick, concrete, mortar, stucco, pavers, and porous stone. LastiSeal™ is a water-based sealer, which penetrates 2-4 inches into concrete and hardens. It internally waterproofs and preserves masonry.

### Safe and Easy to Apply

**Water-based, non-toxic, nonflammable, VOC compliant.**

LastiSeal™ makes bricks and masonry resistant to dirt, spills, freeze-thaw damage, road salts, chemicals, acids, and acid rain. It also reduces water vapor transfer and improves the adhesion as well as life of paints (except latex), adhesives, and coatings.

### COVERAGE

Actual coverage depends on the substrate and porosity.

#### Approximate Coverage (1 application):

200–225 sq. ft./gallon of **indoor concrete**

150–200 sq. ft./gallon of **outdoor concrete and porous masonry**

#### If needed, approximate coverage for a second application:

250–350 sq. ft./gallon

### CONDITIONS

Air and surface temperatures above 45 °F but below 100 °F during and for 24 hours after application. Do not apply to hot surfaces in direct sunlight, or in strong wind. Avoid rain 24 hours before and after application. After pressure washing, let concrete dry for 72 hours.

### SURFACE PREPARATION

**Surface must be dry, clean, and porous!** Remove paints, adhesive, efflorescence, dirt, oil, etc. Concrete must be cured (30 days) and its pH level 5–9. Vacuum excessive dust. Mask glass, metals, tiles, or plants.

### APPLICATION

Apply LastiSeal™ using a low-pressure sprayer (*below 30 psi*) with a fan-pattern nozzle. Spray on a continuous thick glistening film on the verge of puddling. Back-roll puddles or run-downs. If applying with a roller, maintain a wet edge.

For more porous surfaces, apply a lighter second application about half an hour later, provided the first application has readily absorbed. **Tip: If uncertain about sufficient absorption, use only one application.** Ready for foot traffic in several hours and 3 days for vehicles.

### CLEAN UP AND STORAGE

**Clean Up:** Rinse sprayer with water. **Storage:** Keep out of direct sunlight at 40-90 °F. Do not allow to freeze! **Shelf Life:** 1 year.

### USE ONLY AS DIRECTED

**CAUTION:** May irritate eyes and skin. Wash thoroughly after handling.

### KEEP OUT OF REACH OF CHILDREN

#### FIRST AID MEASURES:

**Ingestion:** Drink several glasses of water. Seek medical attention if necessary.

**Eye Contact:** Flush eyes with water for 15 minutes.

**Skin Contact:** Flush with water. Remove contaminated clothing.

**DISCLAIMER:** We shall not be liable for any injury, loss, direct, indirect, or consequential damages arising out of the use of this product. The buyer shall determine the suitability of the product for the intended use and assumes all risk and liability whatsoever in connection with the use of this product.

For detailed application instructions or advice, consult our website or phone us.

## RadonSeal

admin@radonseal.com • 1-800-472-0603 or 203-225-0367  
Novion, Inc. • 18 L'Hermitage Drive • Shelton, CT 06484 • www.radonseal.com