

# ElastiPoxy

Epoxy Joint & Crack Filler

## COMPOUND A – RESIN

State-of-the-art, flexible, two-component epoxy for concrete and masonry repairs. When mixed with sand, provides a strong and rigid repair of concrete floors or walls. Zero VOCs, 100% solids.

### IDEAL FOR THE PERMANENT REPAIR OF:

- Expansion control joints
- Floor-to-wall joints
- Cracks in concrete or brick floors and walls
- Spalls, pits, holes, and defects
- Porous or deteriorated blocks and masonry

**STORAGE:** Store in a cool dry location out of direct sunlight. Shelf life (unopened): 1 year. **Avoid Freezing.**

**DISCLAIMER:** We shall not be liable for any injury, loss, direct, indirect, or consequential damages arising out of the use of this product. The buyer shall determine the suitability of the product for the intended use and assumes all risk and liability whatsoever in connection with the use of this product.

**RadonSeal** Novion, Inc. • 18 L'Hermitage Drive • Shelton, CT 06484  
sales@radonseal.com • 1-800-472-0603 • [www.radonseal.com](http://www.radonseal.com)

**USE ONLY AS DIRECTED. CAUTION. IRRITANT.** May be harmful if swallowed. May be irritating to the eyes, nose and skin. May cause skin sensitization. Take measures to prevent direct contact. Avoid prolonged contact with skin.

### **This product contains:**

BISPHENOL A EPOXY RESIN ..... 25068-38-6  
ALIPHATIC DIGLYCIDYL ETHER..... 26142-30-3

**FIRST AID: Ingestion:** Seek medical attention immediately. Induce vomiting as directed by medical personnel. **Eye Contact:** Flush eyes with water for 15 minutes. Seek medical attention. **Skin Contact:** Flush with water for 15 minutes. Remove contaminated clothing. Consult MSDS for additional safety information. **Inhalation:** Remove to fresh air. Seek medical assistance if necessary.

### **KEEP OUT OF THE REACH OF CHILDREN.**

Contents: 1 quart (946 mL) • Made in USA

# ElastiPoxy

Epoxy Joint & Crack Filler

## COMPOUND B – HARDENER

State-of-the-art, flexible, two-component epoxy for concrete and masonry repairs. When mixed with sand, provides a strong and rigid repair of concrete floors or walls. Zero VOCs, 100% solids.

### IDEAL FOR THE PERMANENT REPAIR OF:

- Expansion control joints
- Floor-to-wall joints
- Cracks in concrete or brick floors and walls
- Spalls, pits, holes, and defects
- Porous or deteriorated blocks and masonry

**STORAGE:** Store in a cool dry location out of direct sunlight. Shelf life (unopened): 1 year. **Avoid Freezing.**

**DISCLAIMER:** We shall not be liable for any injury, loss, direct, indirect, or consequential damages arising out of the use of this product. The buyer shall determine the suitability of the product for the intended use and assumes all risk and liability whatsoever in connection with the use of this product.

**RadonSeal** Novion, Inc. • 18 L'Hermitage Drive • Shelton, CT 06484  
sales@radonseal.com • 1-800-472-0603 • [www.radonseal.com](http://www.radonseal.com)

**USE ONLY AS DIRECTED. CAUTION. IRRITANT.** May be harmful if swallowed. May be irritating to the eyes, nose and skin. May cause skin sensitization. Take measures to prevent direct contact. Avoid prolonged contact with skin.

### **This product contains:**

BENZENEMETHANOL ..... 100-51-6  
TETRAETHYLENE PENTAMINE..... 112-57-2

**FIRST AID: Ingestion:** Seek medical attention immediately. Induce vomiting as directed by medical personnel. **Eye Contact:** Flush eyes with water for 15 minutes. Seek medical attention. **Skin Contact:** Flush with water for 15 minutes. Remove contaminated clothing. Consult MSDS for additional safety information. **Inhalation:** Remove to fresh air. Seek medical assistance if necessary.

### **KEEP OUT OF THE REACH OF CHILDREN.**

Contents: 1 quart (946 mL) • Made in USA